IN THE CLAIMS

Please amend the claims as follows:

- 1.(original) A multi stack optical data storage medium (15) for recording and reading by means of a focused radiation beam (10) entering the medium (15) through a first entrance face (11), said medium having at least a first substrate (1) with on at least one side thereof:
- a first layer stack (2), comprising a first information layer,
- a second layer stack (4), comprising a second information layer, said second layer stack being present at a position closer to the first entrance face (11) than the first layer stack (2), separated from the first layer stack by a first transparent spacer layer (3),
- the first and the second layer stack each having an effective radiation beam reflection Reff between 0.04 and 0.08,
- characterized in that a third layer stack (6), comprising a third information layer, is present at a position closest to the first entrance face (11), separated from the second layer stack (4) by a second transparent spacer layer (5), and said third layer stack having a radiation beam transmission T3 larger than 0.70, and the third information layer is of a type selected from the group of types consisting of a read only layer and a write once layer.
- 2. (original) A multi stack optical data storage medium as claimed in claim 1, wherein at least one of the first and the

second information layer is a rewritable layer.

- 3. (currently amended) A multi stack optical data storage medium as claimed in claim 1 any one of claims 1 or 2, wherein a reflective layer is present adjacent the third information layer comprising a dielectric material.
- 4. (currently amended) A multi stack optical data storage medium as claimed in claim 1 any one of claims 1 3, wherein the third information layer is a read only layer and the third layer stack has a radiation beam transmission T3 between 0.86 and 0.91.
- 5. (currently amended) A multi stack optical data storage medium as claimed in <u>claim 1</u> any one of claims 1 3, wherein the third information layer is a write-once layer and the third layer stack has a radiation beam transmission T3 between 0.81 and 0.84.
- 6. (currently amended) A multi stack optical data storage medium as claimed in claim lany one of claims 1 5, wherein a second radiation beam entrance face opposite to the first entrance face is present for recording and reading by means of a focused radiation beam, entering the medium through the second entrance face, in a fourth, fifth and sixth stack identical to the respectively the first, second and third stack.
- 7. (currently amended) Use of a multi stack optical data storage medium as claimed in <u>claim 1</u> any one of claims 1 6 in a device suitable for recording and reading a dual stack optical data storage medium by means of a focused radiation beam, in which medium the first and the second layer stack each have an effective radiation beam reflection Reff between 0.04 and 0.08.